



VUE-5ER

Mullion Intercom

VUE-5ER

Mullion Intercom

A slim mullion intercom designed for secure entry where space is limited and reliability matters most.

Key Features

- **Slim Mullion Design:** Low-profile form factor designed for narrow door frames and retrofit installations without compromising durability or visibility
- **Mobile-First Calling & Access:** Calls are delivered directly to the MyDoorView mobile app, allowing users to answer, view video, and grant access from anywhere.
- **Guest Access:** Supports secure guest entry through app-based calls and PIN-based access for visitors, deliveries, and temporary access needs.
- **Cloud-Managed Configuration:** Device settings, call routing, and access rules are centrally managed through the MyDoorView platform by authorized partners.



VUE-5ER

Mullion Intercom

LCD Panel

Screen Size	4.58 inches
Resolution	320 x 960 pixels
Panel Type	LED backlight
Brightness	300 cd/m2
Viewing Angle	178°(H) / 178°(W)

Motherboard

CPU	RK3326S
RAM	2GB DDR3
Internal Storage	8GB eMMC
I/O (internal)	1 x micro USB (debug) 1 x upgrade button 1 x upgrade button
I/O (external)	OSDP for Wavelynx Reader OSDP for Motherboard

Pigtail


9 Wire Pigtail	12V out, Input, OSDP RS485A, OSDP RS485B, DC, Relay, REX, 12V in, 24 AWG cable, individual cable strand rated at 7 lbs
----------------	--

Touch

Capacitive Touch	Anti-glare with ceramic baked for UV protection
------------------	---

Power

Power Input	DC 12V/Power over Ethernet
-------------	----------------------------



Operating System

Android	Android
---------	---------

Chassis

Material	Lexan 925U
Color	Black
Working Temperature	IP65, -20° to 60°C (-4° to 140°F)
Impact Resistance	IK07
Dimension	W: 2.13" D: 1.57" H: 8.07"

Reader Technology

Wavelynx Reader	Supported with APEX Module
Credentials	Full compatibility with NFC, Prox, and Bluetooth technologies
LED	Configurable by OSDP

Certifications

Certification	FCC, CE
---------------	---------